

Research Article

Direct Adaptive Tracking Control for a Class of Pure-Feedback Stochastic Nonlinear Systems Based on Fuzzy-Approximation

Huanqing Wang,¹ Xiaoping Liu,^{2,3} Qi Zhou,⁴ and Hamid Reza Karimi⁵

¹ School of Mathematics and Physics, Bohai University, Jinzhou, Liaoning 121000, China

² Faculty of Engineering, Lakehead University, Orillia, Thunder Bay, ON, Canada P7B 5E1

³ Faculty of Electronic and Information Engineering, Liaoning University of Science and Technology, Anshan, Liaoning 114051, China

⁴ College of Information Science and Technology, Bohai University, Jinzhou, Liaoning 121000, China

⁵ Department of Engineering, Faculty of Engineering and Science, University of Agder, 4898 Grimstad, Norway

Correspondence should be addressed to Qi Zhou; zhouqi2009@gmail.com

Received 14 November 2013; Accepted 6 January 2014; Published 13 February 2014

Academic Editor: Xiaojie Su

Copyright © 2014 Huanqing Wang et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

The problem of fuzzy-based direct adaptive tracking control is considered for a class of pure-feedback stochastic nonlinear systems. During the controller design, fuzzy logic systems are used to approximate the packaged unknown nonlinearities, and then a novel direct adaptive controller is constructed via backstepping technique. It is shown that the proposed controller guarantees that all the signals in the closed-loop system are bounded in probability and the tracking error eventually converges to a small neighborhood around the origin in the sense of mean quartic value. The main advantages lie in that the proposed controller structure is simpler and only one adaptive parameter needs to be updated online. Simulation results are used to illustrate the effectiveness of the proposed approach.

1. Introduction

During the past decades, many control methods have been developed to control design of nonlinear systems, such as adaptive control [1–3], backstepping control [4], and fault tolerant control [5–9]. Particularly, backstepping-based adaptive control has been an effective tool to deal with the control problem of nonlinear strict-feedback systems without satisfying matching condition. So far, many interesting results have been obtained for deterministic nonlinear systems in [4, 10–21] and for stochastic cases in [22–35]. In the aforementioned papers, however, the existing results required that the nonlinear functions be in the affine forms; that is, systems are characterized by input appearing linearly in the system state equation.

Pure-feedback nonlinear systems, which have no affine appearance of the state variables that can be used as virtual control and the actual control input, stand for a more representative form than strict-feedback systems. Many practical systems are in nonaffine structure, such as biochemical process [4] and mechanical systems [36]. Therefore, the study on

stability analysis and controller synthesis for pure-feedback nonlinear system is important both in theory and in practice applications [37–42]. By combining adaptive neural control and backstepping, in [37, 38], a class of pure-feedback systems was investigated, which contained only partial nonaffine functions and at least a control variable or virtual control signal existed in affine form. In [39], an “ISS-modular” approach combined with the small-gain theorem was presented for adaptive neural control of completely nonaffine pure-feedback systems. Recently, in [41], an adaptive neural tracking control scheme was presented for a class of nonaffine pure-feedback systems with multiple unknown state time-varying delays. On the other hand, it is well known that stochastic disturbance often exists in practical systems and is usually a source of instability of control systems. So, the consideration of the control design for pure-feedback nonlinear systems with stochastic disturbance is a meaningful issue and has attracted increasing attention in the control community in recent years [43–45]. In [43], the problem of adaptive fuzzy control for pure-feedback stochastic nonlinear systems has been reported. Then, Yu et al. [44] presented an adaptive

neural controller to guarantee the four-moment boundedness for a class of uncertain nonaffine stochastic nonlinear system with time-varying delays. However, the considered systems in [43–45] are of a special kind of pure-feedback stochastic nonlinear systems in which only the last equation was viewed as nonaffine equation.

Motivated by the above observations, we will develop a novel fuzzy-based direct adaptive tracking control scheme for a class of pure-feedback stochastic nonlinear systems. The presented controller guarantees that all the signals in the closed-loop system remain bounded in probability and the tracking error converges to a small neighborhood around the origin in the sense of mean quartic value. The main contributions of this paper lie in that the structure of the proposed controller is simpler and only one adaptive parameter needs to be updated online. As a result, the computational burden is significantly alleviated and the control scheme may be more implemented in practice.

The remainder of this paper is organized as follows. The problem formulation and preliminaries are given in Section 2. An adaptive fuzzy tracking control scheme is presented in Section 3. The simulation example is given in Section 4, and it is followed by Section 5 which concludes the work.

2. Problem Formulation and Preliminaries

To introduce some useful conceptions and lemmas, consider the following stochastic system:

$$dx = f(x, t) dt + h(x, t) dw, \quad \forall x \in R^n, \quad (1)$$

where $x \in R^n$ is state vector, w is a r -dimensional independent standard Brownian motion defined on the complete probability space $(\Omega, F, \{F_t\}_{t \geq 0}, P)$ with Ω being a sample space, F being a σ -field, $\{F_t\}_{t \geq 0}$ being a filtration, and P being a probability measure, and $f : R^n \times R^+ \rightarrow R^n$, $h : R^n \times R^+ \rightarrow R^{n \times r}$ are locally Lipschitz functions in x and satisfy $f(0, t) = 0$, $h(0, t) = 0$.

Definition 1 (see [25]). For any given $V(x, t) \in C^{2,1}$, associated with the stochastic differential equation (1), define the differential operator L as follows:

$$LV = \frac{\partial V}{\partial t} + \frac{\partial V}{\partial x} f + \frac{1}{2} \text{Tr} \left\{ h^T \frac{\partial^2 V}{\partial x^2} h \right\}, \quad (2)$$

where $\text{Tr}(A)$ is the trace of A .

Remark 2. The term $(1/2) \text{Tr}\{h^T(\partial^2 V/(\partial x^2))h\}$ is called Itô correction term, in which the second-order differential $\partial^2 V/\partial x^2$ makes the controller design much more difficult than that of the deterministic system.

Definition 3 (see [46]). The trajectory $\{x(t), t \geq 0\}$ of stochastic system (1) is said to be semiglobally uniformly ultimately bounded in p th moment, if, for some compact set $\Omega \in R^n$ and any initial state $x_0 = x(t_0)$, there exist a constant $\varepsilon > 0$ and a time constant $T = T(\varepsilon, x_0)$ such that $E(|x(t)|^p) < \varepsilon$, for all $t > t_0 + T$. Particularly, when $p = 2$, it is usually called semiglobally uniformly ultimately bounded in mean square.

Lemma 4 (see [46]). Suppose that there exist a $C^{2,1}$ function $V(x, t) : R^n \times R^+ \rightarrow R^+$, two constants $c_1 > 0$ and $c_2 > 0$, and class K_∞ -functions $\bar{\alpha}_1$ and $\bar{\alpha}_2$ such that

$$\begin{aligned} \bar{\alpha}_1(|x|) &\leq V(x, t) \leq \bar{\alpha}_2(|x|), \\ LV(x, t) &\leq -c_1 V(x, t) + c_2, \end{aligned} \quad (3)$$

for all $x \in R^n$ and $t > t_0$. Then, there is a unique strong solution of system (1) for each $x_0 \in R^n$ and it satisfies

$$E[V(x, t)] \leq V(x_0) e^{-c_1 t} + \frac{c_2}{c_1}, \quad \forall t > t_0. \quad (4)$$

In this paper, we consider a class of pure-feedback stochastic nonlinear systems described by

$$\begin{aligned} dx_i &= f_i(\bar{x}_i, x_{i+1}) dt + h_i^T(\bar{x}_i) dw, \quad 1 \leq i \leq n-1, \\ dx_n &= f_n(\bar{x}_n, u) dt + h_n^T(\bar{x}_n) dw, \\ y &= x_1, \end{aligned} \quad (5)$$

where x and w are defined in (1), $u \in R$ and $y \in R$ represent the control input and the system output, and respectively, $\bar{x}_i = [x_1, x_2, \dots, x_i]^T \in R^i$, $f_i(\cdot) : R^{i+1} \rightarrow R$, $h_i(\cdot) : R^i \rightarrow R^r$ ($i = 1, 2, \dots, n$) are unknown smooth nonlinear functions.

The control objective is to design a fuzzy-based adaptive tracking control law u for system (5) such that the system output y follows a desired reference signal y_d in the sense of mean quartic value, and all signals in the closed-loop system remain bounded in probability. To this end, define $\bar{y}_d^{(i)} = [y_d, y_d^{(1)}, \dots, y_d^{(i)}]^T$, $i = 1, 2, \dots, n$, where $y_d^{(i)}$ denotes the i th time derivative of y_d .

For the system (5), define

$$g_i(\bar{x}_i, x_{i+1}) = \frac{\partial f_i(\bar{x}_i, x_{i+1})}{\partial x_{i+1}}, \quad i = 1, 2, \dots, n, \quad (6)$$

where $x_{n+1} = u$.

Assumption 5 (see [42]). The signs of $g_i(\bar{x}_i, x_{i+1})$, $i = 1, 2, \dots, n$, are known, and there exist unknown constants b_m and b_M such that for $1 \leq i \leq n$,

$$0 < b_m \leq |g_i(\bar{x}_i, x_{i+1})| \leq b_M < \infty, \quad \forall (\bar{x}_i, x_{i+1}) \in R^i \times R. \quad (7)$$

Assumption 6 (see [17]). The reference signal $y_d(t)$ and its n th order derivatives are continuous and bounded.

In this note, fuzzy logic system will be used to approximate a continuous function $f(x)$ defined on some compact sets. Adopt the singleton fuzzifier, the product inference, and the center-average defuzzifier to deduce the following fuzzy rules:

$$R_i : \text{IF } x_1 \text{ is } F_1^i \text{ and } x_2 \text{ is } F_2^i \text{ and } \dots \text{ and } x_n \text{ is } F_n^i.$$

Then y is B^i ($i = 1, 2, \dots, N$),

where $x = [x_1, \dots, x_n]^T \in R^n$ and $y \in R$ are the input and output of the fuzzy system, respectively. F_i^j and B^i are fuzzy sets in R . Since the strategy of singleton fuzzification, center-average defuzzification, and product inference is used, the output of the fuzzy system can be formulated as

$$y(x) = \frac{\sum_{j=1}^N \bar{W}_j \prod_{i=1}^n \mu_{F_i^j}(x_i)}{\sum_{j=1}^N \left[\prod_{i=1}^n \mu_{F_i^j}(x_i) \right]}, \quad (8)$$

where \bar{W}_j is the point at which fuzzy membership function $\mu_{B^i}(\bar{W}_j)$ achieves its maximum value, which is assumed to be 1. Let

$$s_j(x) = \frac{\prod_{i=1}^n \mu_{F_i^j}(x_i)}{\sum_{j=1}^N \left[\prod_{i=1}^n \mu_{F_i^j}(x_i) \right]}, \quad (9)$$

$S(x) = [s_1(x), \dots, s_N(x)]^T$, and $W = [\bar{W}_1, \dots, \bar{W}_N]^T$. Then, the fuzzy logic system can be rewritten as

$$y(x) = W^T S(x). \quad (10)$$

If all memberships are chosen as Gaussian functions, the lemma below holds.

Lemma 7 (see [47]). *Let $f(x)$ be a continuous function defined on a compact set Ω . Then, for any given constant $\varepsilon > 0$, there exists a fuzzy logic system (10) such that*

$$\sup_{x \in \Omega} |f(x) - W^T S(x)| \leq \varepsilon. \quad (11)$$

The following lemma will be used in this note.

Lemma 8 (Young's inequality [23]). *For $\forall(x, y) \in R^2$, the following inequality holds:*

$$xy \leq \frac{\varepsilon^p}{p} |x|^p + \frac{1}{q\varepsilon^q} |y|^q, \quad (12)$$

where $\varepsilon > 0$, $p > 1$, $q > 1$, and $(p-1)(q-1) = 1$.

3. Adaptive Fuzzy Control Design

In this section, a fuzzy-based adaptive tracking control scheme is proposed for the system (5). The backstepping design procedure contains n steps and is developed based on the coordinate transformation $z_i = x_i - \alpha_{i-1}$, $i = 1, 2, \dots, n$, where $\alpha_0 = y_d$. The virtual control signal and the adaption law will be constructed in the following forms:

$$\alpha_i = -\frac{1}{2a_i^2} z_i^3 \hat{\theta}, \quad (13)$$

$$\dot{\hat{\theta}} = \sum_{i=1}^n \frac{\sigma}{2a_i^2} z_i^6 - \gamma \hat{\theta}, \quad (14)$$

where a_i ($i = 1, 2, \dots, n$), σ , and γ are positive design parameters and $Z_1 = [x_1, y_d, \dot{y}_d]^T \in \Omega_{Z_1} \subset R^3$, $Z_i =$

$[\bar{x}_i^T, \hat{\theta}, \bar{y}_d^{(i)T}]^T \in \Omega_{Z_i} \subset R^{2i+2}$ ($i = 2, \dots, n$). $\hat{\theta}$ is the estimation of unknown constant θ which is specified as

$$\theta = \max \left\{ \frac{b_M^2}{b_m} \|W_i\|^2; i = 1, 2, \dots, n \right\}. \quad (15)$$

Specially, α_n is the actual control input $u(t)$.

For simplicity, in the following, the time variable t and the state vector \bar{x}_i are omitted from the corresponding functions, and let $S_i(Z_i) = S_i$.

Step 1. Since $z_1 = x_1 - y_d$, the error dynamic satisfies

$$dz_1 = (f_1(x_1, x_2) - \dot{y}_d) dt + h_1^T dw. \quad (16)$$

Consider a Lyapunov function candidate as

$$V_1 = \frac{1}{4} z_1^4 + \frac{b_m}{2\sigma} \bar{\theta}^2, \quad (17)$$

where $\bar{\theta} = \theta - \hat{\theta}$ is the parameter error. By (2) and the completion of squares, one has

$$\begin{aligned} LV_1 &\leq z_1^3 (f_1(x_1, x_2) - \dot{y}_d) + \frac{3z_1^2}{2} h_1^T h_1 - \frac{b_m}{\sigma} \bar{\theta} \dot{\hat{\theta}} \\ &\leq z_1^3 \left(f_1(x_1, x_2) - \dot{y}_d + \frac{3}{4} l_1^{-2} z_1 \|h_1\|^4 \right) \\ &\quad + \frac{3}{4} l_1^2 - \frac{b_m}{\sigma} \bar{\theta} \dot{\hat{\theta}}, \end{aligned} \quad (18)$$

where l_1 is a constant. Define a new function

$$w_1 = -\dot{y}_d + \frac{3}{2} z_1 + k_1 z_1 + \frac{3}{4} l_1^{-2} z_1 \|h_1\|^4, \quad (19)$$

then (18) can be rewritten as

$$\begin{aligned} LV_1 &\leq z_1^3 (f_1(x_1, x_2) + w_1) \\ &\quad - \left(k_1 + \frac{3}{2} \right) z_1^4 + \frac{3}{4} l_1^2 - \frac{b_m}{\sigma} \bar{\theta} \dot{\hat{\theta}}. \end{aligned} \quad (20)$$

Based on Assumption 5 and the fact of $\partial w_1 / \partial x_2 = 0$, one has

$$\frac{\partial [f_1(x_1, x_2) + w_1]}{\partial x_2} \geq b_m > 0. \quad (21)$$

According to Lemma 1 in [37], for each value of x_1 and w_1 , there exists a smooth ideal control input $x_2 = \bar{\alpha}_1(x_1, w_1)$ such that

$$f_1(x_1, \bar{\alpha}_1) + w_1 = 0. \quad (22)$$

Applying mean value theorem [48], there exists μ_1 ($0 < \mu_1 < 1$) which makes

$$f_1(x_1, x_2) = f_1(x_1, \bar{\alpha}_1) + g_{\mu_1}(x_2 - \bar{\alpha}_1), \quad (23)$$

where $g_{\mu_1} := g_1(x_1, x_{\mu_1}) = (\partial f_1(x_1, x_2) / \partial x_2)|_{x_2=x_{\mu_1}}$, $x_{\mu_1} = \mu_1 x_2 + (1 - \mu_1) \bar{\alpha}_1$.

Apparently, Assumption 5 on $g_1(x_1, x_2)$ is still valid for g_{μ_1} . Substituting (23) into (20) and applying the result (22) and $z_2 = x_2 - \alpha_1$ results in

$$\begin{aligned} LV_1 &\leq z_1^3 g_{\mu_1}(x_2 - \bar{\alpha}_1) - \left(k_1 + \frac{3}{2}\right) z_1^4 + \frac{3}{4} l_1^2 - \frac{b_m \bar{\theta} \dot{\theta}}{\sigma} \\ &\leq z_1^3 g_{\mu_1} z_2 + z_1^3 g_{\mu_1} (\alpha_1 - \bar{\alpha}_1) \\ &\quad - \left(k_1 + \frac{3}{2}\right) z_1^4 + \frac{3}{4} l_1^2 - \frac{b_m \bar{\theta} \dot{\theta}}{\sigma}. \end{aligned} \quad (24)$$

Since $\bar{\alpha}_1$ contains the unknown function h_1 , $\bar{\alpha}_1$ cannot be directly implemented in practice. According to Lemma 7, there exists a fuzzy logic system $W_1^T S_1(Z_1)$ which can model the unknown function $\bar{\alpha}_1$ over a compact set $\Omega_{Z_1} \subset R^3$, such that, for any given $\varepsilon_1 > 0$,

$$\bar{\alpha}_1 = W_1^T S_1(Z_1) + \delta_1(Z_1), \quad |\delta_1(Z_1)| \leq \varepsilon_1, \quad (25)$$

where $\delta_1(Z_1)$ is approximation error. Then, based on Young's inequality, it follows that

$$\begin{aligned} -z_1^3 g_{\mu_1} \bar{\alpha}_1 &\leq \frac{b_m z_1^6}{2a_1^2} \frac{\|W_1\|^2}{b_m} S_1^T S_1 + \frac{a_1^2}{2} + \frac{3}{4} z_1^4 + \frac{b_M^4 \varepsilon_1^4}{4} \\ &\leq \frac{b_m}{2a_1^2} z_1^6 \theta + \frac{1}{2} a_1^2 + \frac{3}{4} z_1^4 + \frac{1}{4} b_M^4 \varepsilon_1^4, \end{aligned} \quad (26)$$

where the unknown constant θ is defined in (15) and the property of $S_1^T S_1 \leq 1$ is used in (26). By choosing virtual control signal α_1 in (13) with $i = 1$, and using the property of $\hat{\theta} \geq 0$ and Assumption 5, the following result holds:

$$z_1^3 g_{\mu_1} \alpha_1 \leq -\frac{b_m}{2a_1^2} z_1^6 \hat{\theta}. \quad (27)$$

Substituting (26) and (27) into (20) and using Young's inequality to the term $z_1^3 g_{\mu_1} z_2$ produces

$$LV_1 \leq -k_1 z_1^4 + \frac{1}{4} b_M^4 z_2^4 + \rho_1 + \frac{b_m \bar{\theta}}{\sigma} \left(\frac{\sigma}{2a_1^2} z_1^6 - \hat{\theta} \right), \quad (28)$$

with $\rho_1 = (1/2)a_1^2 + (1/4)b_M^4 \varepsilon_1^4 + (3/4)l_1^2$.

Step 2. Based on the coordinate transformation $z_2 = x_2 - \alpha_1$ and Itô formula, one has

$$dz_2 = (f_2(\bar{x}_2, x_3) - \ell \alpha_1) dt + \left(h_2 - \frac{\partial \alpha_1}{\partial x_1} h_1 \right)^T dw \quad (29)$$

with

$$\ell \alpha_1 = \frac{\partial \alpha_1}{\partial x_1} f_1(x_1, x_2) + \sum_{j=0}^1 \frac{\partial \alpha_1}{\partial y_d^{(j)}} y_d^{(j+1)} + \frac{\partial \alpha_1}{\partial \theta} \dot{\theta} + \frac{1}{2} \frac{\partial^2 \alpha_1}{\partial x_1^2} h_1^T h_1. \quad (30)$$

Take the following Lyapunov function:

$$V_2 = V_1 + \frac{1}{4} z_2^4. \quad (31)$$

Then, by using a similar procedure as Step 1, it follows that

$$\begin{aligned} LV_2 &= LV_1 + z_2^3 (f_2(\bar{x}_2, x_3) - \ell \alpha_1) \\ &\quad + \frac{3}{2} z_2^2 \left(h_2 - \frac{\partial \alpha_1}{\partial x_1} h_1 \right)^T \left(h_2 - \frac{\partial \alpha_1}{\partial x_1} h_1 \right). \end{aligned} \quad (32)$$

It is noticed that

$$\frac{3}{2} z_2^2 \left\| h_2 - \frac{\partial \alpha_1}{\partial x_1} h_1 \right\|^2 \leq \frac{3}{4l_2^2} z_2^4 \left\| h_2 - \frac{\partial \alpha_1}{\partial x_1} h_1 \right\|^4 + \frac{3l_2^2}{4}, \quad (33)$$

where l_2 is a constant.

Furthermore, it can be verified by substituting (28) and (33) into (32) that

$$\begin{aligned} LV_2 &\leq -k_1 z_1^4 + \frac{b_m \bar{\theta}}{\sigma} \left(\frac{\sigma}{2a_1^2} z_1^6 - \hat{\theta} \right) \\ &\quad + z_2^3 \left(f_2(\bar{x}_2, x_3) - \ell \alpha_1 + \frac{3z_2}{4l_2^2} \left\| h_2 - \frac{\partial \alpha_1}{\partial x_1} h_1 \right\|^4 \right. \\ &\quad \left. + \frac{1}{4} b_M^4 z_2 \right) + \rho_1 + \frac{3}{4} l_2^2. \end{aligned} \quad (34)$$

From the definition of $\hat{\theta}$ in (14), we have

$$\frac{\partial \alpha_1}{\partial \theta} \hat{\theta} = \frac{\partial \alpha_1}{\partial \theta} \left(\sum_{j=1}^2 \frac{\sigma}{2a_j^2} z_j^6 - \gamma \hat{\theta} \right) + \frac{\partial \alpha_1}{\partial \theta} \sum_{j=3}^n \frac{\sigma}{2a_j^2} z_j^6. \quad (35)$$

By combining (30), (34), and (35), the following result holds:

$$\begin{aligned} LV_2 &\leq -k_1 z_1^4 + \rho_1 + z_2^3 (f_2(\bar{x}_2, x_3) + w_2) \\ &\quad - \left(k_2 + \frac{3}{2} \right) z_2^4 + \frac{b_m \bar{\theta}}{\sigma} \left(\frac{\sigma}{2a_1^2} z_1^6 - \hat{\theta} \right) \\ &\quad - \frac{\partial \alpha_1}{\partial \theta} z_2^3 \sum_{j=3}^n \frac{\sigma}{2a_j^2} z_j^6 + \frac{3}{4} l_2^2, \end{aligned} \quad (36)$$

where

$$\begin{aligned} w_2 &= \frac{b_M^4}{4} z_2 - \frac{\partial \alpha_1}{\partial x_1} f_2(x_1, x_2) \\ &\quad - \sum_{j=0}^1 \frac{\partial \alpha_1}{\partial y_d^{(j)}} y_d^{(j+1)} - \frac{1}{2} \frac{\partial^2 \alpha_1}{\partial x_1^2} h_1^T h_1 \\ &\quad + \frac{3}{4} l_2^2 z_2 \left\| h_2 - \frac{\partial \alpha_1}{\partial x_1} h_1 \right\|^4 \\ &\quad - \frac{\partial \alpha_1}{\partial \theta} \left(\sum_{j=1}^2 \frac{\sigma}{2a_j^2} z_j^6 - \sigma \hat{\theta} \right) + \left(k_2 + \frac{3}{2} \right) z_2. \end{aligned} \quad (37)$$

It can be seen from (37) that $\partial w_2 / \partial x_3 = 0$. Then, from Assumption 5, we have

$$\frac{\partial [f_2(\bar{x}_2, x_3) + w_2]}{\partial x_3} \geq b_m > 0. \quad (38)$$

According to Lemma 1 in [37], there exists a smooth ideal control input $x_3 = \bar{\alpha}_2(\bar{x}_2, w_2)$ such that

$$f_2(\bar{x}_2, \bar{\alpha}_2) + w_2 = 0. \quad (39)$$

By applying mean value theorem [48], there exists μ_2 ($0 < \mu_2 < 1$) such that

$$f_2(\bar{x}_2, x_3) = f_2(\bar{x}_2, \bar{\alpha}_2) + g_{\mu_2}(x_3 - \bar{\alpha}_2), \quad (40)$$

where $g_{\mu_2} = (\partial f_2(\bar{x}_2, x_3)/\partial x_3)|_{x_3=x_{\mu_2}}$, $x_{\mu_2} = \mu_2 x_3 + (1 - \mu_2)\bar{\alpha}_2$. Assumption 5 on $g_2(\bar{x}_2, x_3)$ is still valid for g_{μ_2} .

Substituting (39) and (40) into (36) produces

$$\begin{aligned} LV_2 \leq & -k_1 z_1^4 + \rho_1 + z_2^3 g_{\mu_2} z_3 + z_2^3 g_{\mu_2} (\alpha_2 - \bar{\alpha}_2) \\ & - \left(k_2 + \frac{3}{2} \right) z_2^4 + \frac{b_m \tilde{\theta}}{\sigma} \left(\frac{\sigma}{2a_1^2} z_1^6 - \dot{\hat{\theta}} \right) \\ & - \frac{\partial \alpha_1}{\partial \hat{\theta}} z_2^3 \sum_{j=3}^n \frac{\sigma}{2a_j^2} z_j^6 + \frac{3}{4} l_2^2, \end{aligned} \quad (41)$$

where $z_3 = x_3 - \alpha_2$.

Further, fuzzy logic system $W_2^T S(Z_2)$ is used to approximate the desired unknown virtual signal $\bar{\alpha}_i$ over a compact set $\Omega_{Z_2} \subset R^6$ such that, for any given positive constant ε_i , $\bar{\alpha}_2$ can be shown as

$$\bar{\alpha}_2 = W_2^T S_2(Z_2) + \delta_2(Z_2), \quad |\delta_2(Z_2)| \leq \varepsilon_2, \quad (42)$$

with $\delta_2(Z_2)$ being the approximation error.

Then, constructing the virtual control signal α_2 in (13) and repeating the same methods used in (26) and (27), one has

$$\begin{aligned} -z_2^3 g_{\mu_2} \bar{\alpha}_2 & \leq \frac{b_m}{2a_2^2} z_2^6 \theta + \frac{1}{2} a_2^2 + \frac{3}{4} z_2^4 + \frac{1}{4} b_M^4 \varepsilon_2^4, \\ z_2^3 g_{\mu_2} \alpha_2 & \leq -\frac{b_m}{2a_2^2} z_2^6 \hat{\theta}. \end{aligned} \quad (43)$$

By taking (43) into account and using Young's inequality to the term $z_2^3 g_{\mu_2} z_3$, (41) can be rewritten as

$$\begin{aligned} LV_2 \leq & \sum_{j=1}^2 (-k_j z_j^4 + \rho_j) + \frac{b_m \tilde{\theta}}{\sigma} \left(\sum_{j=1}^2 \frac{\sigma}{2a_j^2} z_j^6 - \dot{\hat{\theta}} \right) \\ & - \frac{\partial \alpha_1}{\partial \hat{\theta}} z_2^3 \sum_{j=3}^n \frac{\sigma}{2a_j^2} z_j^6 + \frac{1}{4} b_M^4 z_3^4, \end{aligned} \quad (44)$$

where $\rho_j = (1/2)a_j^2 + (1/4)b_M^4 \varepsilon_j^4 + (3/4)l_j^2$, $j = 1, 2$.

Remark 9. The adaptive law $\hat{\theta}$ defined in (14) is a function of all the error variables. So, unlike the conventional approximation-based adaptive control schemes, $(\partial \alpha_1 / \partial \hat{\theta}) \dot{\hat{\theta}}$ in (30) cannot be approximated directly by fuzzy logic system $W_2^T S_2(Z_2)$. To solve this problem, in (35), $(\partial \alpha_1 / \partial \hat{\theta}) \dot{\hat{\theta}}$ is divided into two parts. The first term in the right hand side

of (35) is contained in $\bar{\alpha}_2$ to be modeled by $W_2^T S_2(Z_2)$, and the last term in (35) which is a function of the latter error variables, namely, z_j , $j = 3, 4, \dots, n$, will be dealt with in the later design steps. This design idea will be repeated at the following steps.

Step i ($3 \leq i \leq n - 1$). From $z_i = x_i - \alpha_{i-1}$ and Itô formula, we have

$$dz_i = (f_i(\bar{x}_i, x_{i+1}) - \ell \alpha_{i-1}) dt + \left(h_i - \sum_{j=1}^{i-1} \frac{\partial \alpha_{i-1}}{\partial x_j} h_j \right)^T dw, \quad (45)$$

where

$$\begin{aligned} \ell \alpha_{i-1} = & \sum_{j=1}^{i-1} \frac{\partial \alpha_{i-1}}{\partial x_j} f_j(\bar{x}_j, x_{j+1}) + \sum_{j=0}^{i-1} \frac{\partial \alpha_{i-1}}{\partial y_d^{(j)}} y_d^{(j+1)} \\ & + \frac{\partial \alpha_{i-1}}{\partial \hat{\theta}} \dot{\hat{\theta}} + \frac{1}{2} \sum_{p,q=1}^{i-1} \frac{\partial^2 \alpha_{i-1}}{\partial x_p \partial x_q} h_p^T h_q. \end{aligned} \quad (46)$$

Choose a Lyapunov function as

$$V_i = V_{i-1} + \frac{1}{4} z_i^4. \quad (47)$$

Then, it follows that

$$\begin{aligned} LV_i = & LV_{i-1} + z_i^3 (f_i(\bar{x}_i, x_{i+1}) - \ell \alpha_{i-1}) \\ & + \frac{3}{2} z_i^2 \left(h_i - \sum_{j=1}^{i-1} \frac{\partial \alpha_{i-1}}{\partial x_j} h_j \right)^T \\ & \times \left(h_i - \sum_{j=1}^{i-1} \frac{\partial \alpha_{i-1}}{\partial x_j} h_j \right), \end{aligned} \quad (48)$$

where the term LV_{i-1} in (48) can be obtained in the following form by straightforward derivations as those in former steps:

$$\begin{aligned} LV_{i-1} \leq & \sum_{j=1}^{i-1} (-k_j z_j^4 + \rho_j) + \frac{b_m \tilde{\theta}}{\sigma} \left(\sum_{j=1}^{i-1} \frac{\sigma}{2a_j^2} z_j^6 - \dot{\hat{\theta}} \right) \\ & - \sum_{m=1}^{i-2} \frac{\partial \alpha_m}{\partial \hat{\theta}} z_{m+1}^3 \sum_{j=1}^n \frac{\sigma}{2a_j^2} z_j^6 + \frac{b_M^4}{4} z_i^4, \end{aligned} \quad (49)$$

where $\rho_j = (1/2)a_j^2 + (1/4)b_M^4 \varepsilon_j^4 + (3/4)l_j^2$.

According to the definition of $\hat{\theta}$ in (14), one has

$$\frac{\partial \alpha_{i-1}}{\partial \hat{\theta}} \dot{\hat{\theta}} = \frac{\partial \alpha_{i-1}}{\partial \hat{\theta}} \left(\sum_{j=1}^i \frac{\sigma}{2a_j^2} z_j^6 - \gamma \hat{\theta} \right) + \frac{\partial \alpha_{i-1}}{\partial \hat{\theta}} \sum_{j=i+1}^n \frac{\sigma}{2a_j^2} z_j^6. \quad (50)$$

Then, substituting (49) into (48) and taking (50) into account, (48) can be rewritten as

$$\begin{aligned} LV_i \leq & \sum_{j=1}^{i-1} (-k_j z_j^4 + \rho_j) + z_i^3 (f_i(\bar{x}_i, x_{i+1}) + w_i) \\ & - \left(k_i + \frac{3}{2} \right) z_i^4 + \frac{b_m \bar{\theta}}{\sigma} \left(\sum_{j=1}^{i-1} \frac{\sigma}{2a_j^2} z_j^6 - \dot{\bar{\theta}} \right) \\ & - \sum_{m=1}^{i-1} \frac{\partial \alpha_m}{\partial \bar{\theta}} z_{m+1}^3 \sum_{j=i+1}^n \frac{\sigma}{2a_j^2} z_j^6 + \frac{3}{4} l_i^2, \end{aligned} \quad (51)$$

where

$$\begin{aligned} w_i = & \frac{b_M^4}{4} z_i - \sum_{j=1}^{i-1} \frac{\partial \alpha_{i-1}}{\partial x_j} f_j(\bar{x}_j, x_{j+1}) \\ & - \sum_{j=0}^{i-1} \frac{\partial \alpha_{i-1}}{\partial y_d^{(j)}} y_d^{(j+1)} - \frac{1}{2} \sum_{p,q=1}^{i-1} \frac{\partial^2 \alpha_{i-1}}{\partial x_p \partial x_q} h_p^T h_q \\ & + \frac{3}{4} l_i^2 z_i \left\| h_i - \sum_{j=1}^{i-1} \frac{\partial \alpha_{i-1}}{\partial x_j} h_j \right\|^4 \\ & - \frac{\partial \alpha_{i-1}}{\partial \bar{\theta}} \left(\sum_{j=1}^i \frac{\sigma}{2a_j^2} z_j^6 - \sigma \bar{\theta} \right) \\ & - \frac{\sigma}{2a_i^2} z_i^3 \sum_{m=1}^{i-2} \frac{\partial \alpha_m}{\partial \bar{\theta}} z_{m+1}^3 + \left(k_i + \frac{3}{2} \right) z_i. \end{aligned} \quad (52)$$

Noting $\partial w_i / \partial x_{i+1} = 0$, it follows that

$$\frac{\partial [f_i(\bar{x}_i, x_{i+1}) + w_i]}{\partial x_{i+1}} \geq b_m > 0. \quad (53)$$

Based on Lemma 1 in [37], there exists a smooth ideal control input $x_{i+1} = \bar{\alpha}_i(\bar{x}_i, w_i)$ which makes

$$f_i(\bar{x}_i, \bar{\alpha}_i) + w_i = 0. \quad (54)$$

In addition, applying mean value theorem [48], there exists μ_i ($0 < \mu_i < 1$) such that

$$f_i(\bar{x}_i, x_{i+1}) = f_i(\bar{x}_i, \bar{\alpha}_i) + g_{\mu_i}(x_{i+1} - \bar{\alpha}_i), \quad (55)$$

where $g_{\mu_i} = (\partial f_i(\bar{x}_i, x_{i+1}) / \partial x_{i+1})|_{x_{i+1}=x_{\mu_i}}$, $x_{\mu_i} = \mu_i x_{i+1} + (1 - \mu_i) \bar{\alpha}_i$. Assumption 5 on $g_i(\bar{x}_i, x_{i+1})$ is still valid for g_{μ_i} . Combining (51)–(55) yields

$$\begin{aligned} LV_i \leq & \sum_{j=1}^{i-1} (-k_j z_j^4 + \rho_j) + z_i^3 g_{\mu_i} z_{i+1} + z_i^3 g_{\mu_i} (\alpha_i - \bar{\alpha}_i) \\ & - \left(k_i + \frac{3}{2} \right) z_i^4 + \frac{b_m \bar{\theta}}{\sigma} \left(\sum_{j=1}^{i-1} \frac{\sigma}{2a_j^2} z_j^6 - \dot{\bar{\theta}} \right) \\ & - \sum_{m=1}^{i-1} \frac{\partial \alpha_m}{\partial \bar{\theta}} z_{m+1}^3 \sum_{j=i+1}^n \frac{\sigma}{2a_j^2} z_j^6 + \frac{3}{4} l_i^2, \end{aligned} \quad (56)$$

where $z_{i+1} = x_{i+1} - \alpha_i$. Subsequently, using fuzzy logic system $W_i^T S(Z_i)$ to model $\bar{\alpha}_i$ over a compact set $\Omega_{Z_i} \subset R^{2i+2}$ such that for any given $\varepsilon_i > 0$, $\bar{\alpha}_i$ can be expressed as

$$\bar{\alpha}_i = W_i^T S_i(Z_i) + \delta_i(Z_i), \quad |\delta_i(Z_i)| \leq \varepsilon_i, \quad (57)$$

with $\delta_i(Z_i)$ being the approximation error. Furthermore, constructing virtual control signal α_i in (13) and following the same line as the procedures used from (26) to (27), one has

$$\begin{aligned} -z_i^3 g_{\mu_i} \bar{\alpha}_i \leq & \frac{b_m}{2a_i^2} z_i^6 \theta + \frac{1}{2} a_i^2 + \frac{3}{4} z_i^4 + \frac{1}{4} b_M^4 \varepsilon_i^4, \\ z_i^3 g_{\mu_i} \alpha_i \leq & -\frac{b_m}{2a_i^2} z_i^6 \hat{\theta}. \end{aligned} \quad (58)$$

By substituting (58) into (56) and using Young's inequality, we have

$$\begin{aligned} LV_i \leq & \sum_{j=1}^i (-k_j z_j^4 + \rho_j) + \frac{b_m \bar{\theta}}{\sigma} \left(\sum_{j=1}^i \frac{\sigma}{2a_j^2} z_j^6 - \dot{\bar{\theta}} \right) \\ & - \sum_{m=1}^{i-1} \frac{\partial \alpha_m}{\partial \bar{\theta}} z_{m+1}^3 \sum_{j=i+1}^n \frac{\sigma}{2a_j^2} z_j^6 + \frac{1}{4} b_M^4 z_{i+1}^4, \end{aligned} \quad (59)$$

where $\rho_j = (1/2)a_j^2 + (1/4)b_M^4 \varepsilon_j^4 + (3/4)l_j^2$.

Step n. In this step, the actual control input signal u will be obtained. By $z_n = x_n - \alpha_{n-1}$ and Itô formula, we have

$$dz_n = (f_n(\bar{x}_n, u) - \ell \alpha_{n-1}) dt + \left(h_n - \sum_{j=1}^{n-1} \frac{\partial \alpha_{n-1}}{\partial x_j} h_j \right)^T dw, \quad (60)$$

where $\ell \alpha_{n-1}$ is defined in (46) with $i = n$. Choosing the Lyapunov function

$$V_n = V_{n-1} + \frac{1}{4} z_n^4, \quad (61)$$

then, the following inequality can be easily verified by using (2), the completion of squares, and taking (59) with $i = n - 1$ into account:

$$\begin{aligned} LV_n \leq & \sum_{j=1}^{n-1} (-k_j z_j^4 + \rho_j) + \frac{b_m \bar{\theta}}{\sigma} \left(\sum_{j=1}^{n-1} \frac{\sigma}{2a_j^2} z_j^6 - \dot{\bar{\theta}} \right) \\ & + z_n^3 (f_n(\bar{x}_n, u) + w_n) - \left(k_n + \frac{3}{4} \right) z_n^4 + \frac{3}{4} l_n^2, \end{aligned} \quad (62)$$

where

$$\begin{aligned} w_n = & \ell \alpha_{n-1} - \sum_{m=1}^{n-2} \frac{\partial \alpha_m}{\partial \bar{\theta}} z_{m+1}^3 \frac{\sigma}{2a_n^2} z_n^3 + \frac{1}{4} b_M^4 z_n \\ & + \frac{3}{4} l_n^2 z_n \left\| h_n - \sum_{j=1}^{n-1} \frac{\partial \alpha_{n-1}}{\partial x_j} h_j \right\|^4 + \left(k_n + \frac{3}{4} \right) z_n. \end{aligned} \quad (63)$$

From the definition of w_n , Assumption 5 and Lemma 1 in [37], for every value \bar{x}_n and w_n , there exists a smooth ideal control input $u = \bar{\alpha}_n(\bar{x}_n, w_n)$ such that $f_n(\bar{x}_n, \bar{\alpha}_n) + w_n = 0$. By using mean value theorem [48], there exists μ_n ($0 < \mu_n < 1$) such that

$$f_n(\bar{x}_n, u) = f_i(\bar{x}_n, \bar{\alpha}_n) + g_{\mu_n}(u - \bar{\alpha}_n), \quad (64)$$

where $g_{\mu_n} = (\partial f_n(\bar{x}_n, u)/\partial u)|_{u=x_{\mu_n}}$, $x_{\mu_n} = \mu_n u + (1 - \mu_n)\bar{\alpha}_n$.

Furthermore, (62) can be rewritten as

$$LV_n \leq \sum_{j=1}^{n-1} (-k_j z_j^4 + \rho_j) + \frac{b_m \bar{\theta}}{\sigma} \left(\sum_{j=1}^{n-1} \frac{\sigma}{2a_j^2} z_j^6 - \dot{\hat{\theta}} \right) + z_n^3 g_{\mu_n}(u - \bar{\alpha}_n) - \left(k_n + \frac{3}{4} \right) z_n^4 + \frac{3}{4} l_n^2. \quad (65)$$

Next, using fuzzy logic system $W_n^T S(Z_n)$ to approximate the unknown function $\bar{\alpha}_n$ on the compact set $\Omega_{Z_n} \subset R^{2n+2}$, constructing the actual control u in (13) with $i = n$, and repeating the same procedures as (58)-(59), one has

$$LV_n \leq \sum_{j=1}^n (-k_j z_j^4 + \rho_j) + \frac{b_m \bar{\theta}}{\sigma} \left(\sum_{j=1}^n \frac{\sigma}{2a_j^2} z_j^6 - \dot{\hat{\theta}} \right). \quad (66)$$

Further, choosing the adaptive law $\dot{\hat{\theta}}$ in (14) and using the inequality $(\gamma b_m / \sigma) \bar{\theta} \dot{\hat{\theta}} \leq -(\gamma b_m / 2\sigma) \bar{\theta}^2 + (\gamma b_m / 2\sigma) \theta^2$ result in

$$LV_n \leq -\sum_{j=1}^n k_j z_j^4 - \frac{\gamma b_m}{2\sigma} \bar{\theta}^2 + \sum_{j=1}^n \rho_j + \frac{\gamma b_m}{2\sigma} \theta^2, \quad (67)$$

where $\rho_j = (1/2)a_j^2 + (1/4)b_M^4 \varepsilon_j^4 + (3/4)l_j^2$, $j = 1, 2, \dots, n$.

Now, the actual control signal u is constructed. The main result will be summarized by the following theorem.

Theorem 10. Consider the pure-feedback stochastic nonlinear system (5), the controller (13), and adaptive law (14) under Assumptions 5 and 6. Assume that there exists sufficiently large compacts Ω_{Z_i} , $i = 1, 2, \dots, n$, such that $Z_i \in \Omega_{Z_i}$ for all $t \geq 0$; then, for bounded initial conditions $[\bar{z}_n(0)^T, \hat{\theta}(0)^T]^T \in \Omega_0$ (where Ω_0 is an appropriately chosen compact set),

- (i) all the signals in the closed-loop system are bounded in probability;
- (ii) there exists a finite time T_1 such that the quartic mean square tracking error enters inside the area for all $t > T_1$,

$$\Omega_1 = \{y(t) \in R \mid E[|y - y_d|^4] \leq 8\rho, \forall t > T_1\}, \quad (68)$$

where the time T_1 will be given later.

Proof. (i) For the stability analysis of the closed-loop system, choose the Lyapunov function as $V = V_n$. From (67), it follows that

$$LV \leq -a_0 V + b_0, \quad (69)$$

where $a_0 = \min\{4k_j, \gamma, j = 1, 2, \dots, n\}$ and $b_0 = \sum_{j=1}^n \rho_j + (\gamma b_m / 2\sigma) \theta^2$. Therefore, based on Lemma 4 in [37], z_j and $\hat{\theta}$ remain bounded in probability. Because θ is a constant, $\hat{\theta}$ is bounded in probability. It can be further seen that α_j is a function of z_j and $\hat{\theta}$. So, α_j is also bounded in probability. Hence, we conclude that all the signals x_j in the closed-loop system (5) remain bounded in the sense of probability.

(ii) From (69), the following inequality can be obtained directly by [24, Theorem 4.1]

$$\frac{dE[V(t)]}{dt} \leq -a_0 E[V(t)] + b_0. \quad (70)$$

Let $\rho := b_0/a_0 > 0$, then (70) satisfies

$$0 \leq E[V(t)] \leq V(0) e^{-a_0 t} + \rho. \quad (71)$$

Then, it can be easily verified that there exists a time $T_1 = \max\{0, (1/a_0) \ln(V(0)/\rho)\}$ such that

$$E[|y - y_d|^4] \leq 4E[V(t)] \leq 8\rho, \quad \forall t > T_1. \quad (72)$$

□

4. Simulation Results

In this section, to illustrate the effectiveness of the proposed control scheme, we consider the following second-order pure-feedback stochastic nonlinear system:

$$\begin{aligned} dx_1 &= (x_2 + 0.05 \sin(x_2)) dt + 0.1 \cos(x_1) dw, \\ dx_2 &= \left(\left(2 + \frac{x_1^2}{1 + x_1^2 + x_2^2} \right) u + 0.1u^3 \right) dt \\ &\quad + 0.2 \sin(x_1 x_2) dw, \\ y &= x_1. \end{aligned} \quad (73)$$

The control objective is to design an adaptive controller for the system such that all the signals in the closed-loop system remain bounded and the system output y tracks the given reference signal $y_d = 0.5(\sin(t) + \sin(0.5t))$. According to Theorem 10, choose the virtual control law α_1 in (13), actual control input u in (13) with $i = 2$, and adaptive law in (14). The design parameters are taken as follows: $a_1 = a_2 = 0.06$, $\gamma = 0.0015$, and $\sigma = 25$. The initial conditions are given by $[x_1(0), x_2(0)]^T = [0.2, 0.5]^T$ and $\hat{\theta}(0) = 0$.

The simulation results are shown in Figures 1–4. Figure 1 shows the system output y and the reference signal y_d . Figure 2 and Figure 3 show that the state variable x_2 and adaptive parameter $\hat{\theta}$ are bounded. Figure 4 displays the control input signal u .

5. Conclusions

In this paper, a novel fuzzy-based adaptive control scheme has been presented for pure-feedback stochastic nonlinear systems. The proposed controller guarantees that all the signals in the closed-loop systems are bounded in probability




FIGURE 1: System output y and reference signal y_d .




FIGURE 2: The state variable x_2 .

and tracking error eventually converges to a small neighborhood around the origin in the sense of mean quartic value. The main advantages of this control scheme are that the controller is simpler than the existing ones and only one adaptive parameter needs to be estimated online for an n -order system. Numerical results have been provided to show the effectiveness of the suggested approach. Our future research will mainly focus on the multi-input and multi-output (MIMO) pure-feedback stochastic nonlinear systems based on the result in this paper.

Conflict of Interests

The authors declare that there is no conflict of interests regarding the publication of this paper.




FIGURE 3: The adaptive parameter $\hat{\theta}$.




FIGURE 4: The true control input u .

Acknowledgments

This work is partially supported by the Natural Science Foundation of China (61304002, 61304003, and 11371071), the Program for New Century Excellent Talents in University (NECT-13-0696), the Program for Liaoning Innovative Research Team in University under Grant (LT2013023), the Program for Liaoning Excellent Talents in University under Grant (LR2013053), and the Education Department of Liaoning Province under the general project research under Grant (no. L2013424).

References

- [1] K. S. Narendra and A. M. Annaswamy, *Stable Adaptive Systems*, Prentice-Hall, Englewood Cliffs, NJ, USA, 1989.

- [2] H. Y. Li, J. Y. Yu, C. Hilton, and H. H. Liu, "Adaptive sliding mode control for nonlinear active suspension vehicle systems using T-S fuzzy Approach," *IEEE Transactions on Industrial Electronics*, vol. 60, no. 8, pp. 3328–3338, 2013.
- [3] H. Y. Li, J. Y. Yu, C. Hilton, and H. H. Liu, "Adaptive sliding mode control for nonlinear active suspension vehicle systems using T-S fuzzy approach," *IEEE Transactions on Industrial Electronics*, vol. 60, no. 8, pp. 3328–3338, 2013.
- [4] M. Krstic, I. Kanellakopoulos, and P. V. Kokotovic, *Nonlinear and Adaptive Control Design*, Wiley, New York, NY, USA, 1995.
- [5] M. Liu, X. Cao, and P. Shi, "Fault estimation and tolerant control for fuzzy stochastic systems," *IEEE Transactions on Fuzzy Systems*, vol. 21, no. 2, pp. 221–2229, 2013.
- [6] M. Liu, X. Cao, and P. Shi, "Fuzzy-model-based fault tolerant design for nonlinear stochastic systems against simultaneous sensor and actuator faults," *IEEE Transactions on Fuzzy Systems*, vol. 21, no. 5, pp. 789–799, 2013.
- [7] S. Yin, S. Ding, and H. Luo, "Real-time implementation of fault tolerant control system with performance optimization," *IEEE Transactions on Industrial Electronics*, vol. 61, no. 5, pp. 2402–2411, 2013.
- [8] S. Yin, S. Ding, A. Haghani, H. Hao, and P. Zhang, "A comparison study of basic data-driven fault diagnosis and process monitoring methods on the benchmark Tennessee Eastman process," *Journal of Process Control*, vol. 22, no. 9, pp. 1567–1581, 2012.
- [9] H. Li, H. Liu, H. Gao, and P. Shi, "Reliable fuzzy control for active suspension systems with actuator delay and fault," *IEEE Transactions on Fuzzy Systems*, vol. 20, no. 2, pp. 342–357, 2012.
- [10] H. Y. Li, X. J. Jing, H. K. Lam, and P. Shi, "Fuzzy Sampled-data control for uncertain vehicle suspension systems," *IEEE Transactions on Cybernetics*, 2013.
- [11] H. Y. Li, X. J. Jing, and H. R. Karimi, "Output-feedback based h-infinity control for active suspension systems with control delay," *IEEE Transactions on Industrial Electronics*, vol. 61, no. 1, pp. 436–446, 2014.
- [12] M. Chen, S. S. Ge, B. V. E. How, and Y. S. Choo, "Robust adaptive position mooring control for marine vessels," *IEEE Transactions on Control Systems Technology*, vol. 21, no. 2, pp. 395–409, 2013.
- [13] S. Bououden, M. Chadli, F. Allouani, and S. Filali, "A new approach for fuzzy predictive adaptive controller design using particle swarm optimization algorithm," *International Journal of Innovative Computing, Information and Control*, vol. 9, no. 9, pp. 3741–3758, 2013.
- [14] S. Sefriti, J. Boumhidi, M. Benyakhlef, and I. Boumhidi, "Adaptive decentralized sliding mode neural network control of a class of nonlinear interconnected systems," *International Journal of Innovative Computing, Information and Control*, vol. 9, no. 7, pp. 2941–2947, 2013.
- [15] C. M. Lin, C. F. Hsu, and R. G. Yeh, "Adaptive fuzzy sliding-mode control system design for brushless DC motors," *International Journal of Innovative Computing, Information and Control*, vol. 9, no. 3, pp. 1259–1270, 2013.
- [16] T. Shaocheng, C. Bin, and W. Yongfu, "Fuzzy adaptive output feedback control for MIMO nonlinear systems," *Fuzzy Sets and Systems*, vol. 156, no. 2, pp. 285–299, 2005.
- [17] B. Chen, X. Liu, K. Liu, and C. Lin, "Direct adaptive fuzzy control of nonlinear strict-feedback systems," *Automatica*, vol. 45, no. 6, pp. 1530–1535, 2009.
- [18] B. Chen, X.-P. Liu, S.-C. Tong, and C. Lin, "Observer-based stabilization of T-S fuzzy systems with input delay," *IEEE Transactions on Fuzzy Systems*, vol. 16, no. 3, pp. 652–663, 2008.
- [19] X. D. Zhao, L. X. Zhang, P. Shi, and H. R. Karimi, "Novel stability criteria for T-S fuzzy systems," *IEEE Transactions on Fuzzy Systems*, vol. 21, no. 6, pp. 1–11, 2013.
- [20] X. J. Su, P. Shi, L. Wu, and Y. Song, "A novel approach to filter design for T-S fuzzy discretetime systems with time-varying delay," *IEEE Transactions on Fuzzy Systems*, vol. 20, no. 6, pp. 1114–1129, 2012.
- [21] X. J. Su, P. Shi, L. Wu, and Y. -D. Song, "A novel control design on discrete-time Takagi- Sugeno fuzzy systems with time-varying delays," *IEEE Trans on Fuzzy Systems*, vol. 20, no. 6, pp. 655–671, 2013.
- [22] X. J. Su, P. Shi, L. Wu, and S. K. Nguang, "Induced ℓ_2 filtering of fuzzy stochastic systems with time-varying delays," *IEEE Transactions on Cybernetics*, vol. 43, no. 4, pp. 1251–1264, 2013.
- [23] H. Deng and M. Krstić, "Stochastic nonlinear stabilization. I. A backstepping design," *Systems & Control Letters*, vol. 32, no. 3, pp. 143–150, 1997.
- [24] H. Deng, M. Krstić, and R. J. Williams, "Stabilization of stochastic nonlinear systems driven by noise of unknown covariance," *IEEE Transactions on Automatic Control*, vol. 46, no. 8, pp. 1237–1253, 2001.
- [25] S.-J. Liu, J.-F. Zhang, and Z.-P. Jiang, "Decentralized adaptive output-feedback stabilization for large-scale stochastic nonlinear systems," *Automatica*, vol. 43, no. 2, pp. 238–251, 2007.
- [26] L. Liu and X.-J. Xie, "Output-feedback stabilization for stochastic high-order nonlinear systems with time-varying delay," *Automatica*, vol. 47, no. 12, pp. 2772–2779, 2011.
- [27] L. Liu, N. Duan, and X.-J. Xie, "Output-feedback stabilization for stochastic high-order nonlinear systems with a ratio of odd integers power," *Acta Automatica Sinica*, vol. 36, no. 6, pp. 858–864, 2010.
- [28] Z. Wu, M. Cui, P. Shi, and H. R. Karimi, "Stability of stochastic nonlinear systems with state-dependent switching," *IEEE Transactions on Automatic Control*, vol. 58, no. 8, pp. 1904–1918, 2013.
- [29] H. R. Karimi, "Robust delay-dependent H_∞ control of uncertain time-delay systems with mixed neutral, discrete, and distributed time-delays and Markovian switching parameters," *IEEE Transactions on Circuits and Systems. I*, vol. 58, no. 8, pp. 1910–1923, 2011.
- [30] S. Huang, Z. Xiang, and H. R. Karimi, "Robust L_2 -gain control for 2D nonlinear stochastic systems with time-varying delays and actuator saturation," *Journal of the Franklin Institute*, vol. 350, no. 7, pp. 1865–1885, 2013.
- [31] H. E. Psillakis and A. T. Alexandridis, "Adaptive neural tracking for a class of SISO uncertain and stochastic nonlinear systems," in *Proceedings of the 44th IEEE Conference on Decision and Control, and the European Control Conference (CDC-ECC '05)*, pp. 7822–7827, Seville, Spain, December 2005.
- [32] Q. Zhou, P. Shi, H. H. Liu, and S. Y. Xu, "Neural-network-based decentralized adaptive output-feedback control for large-scale stochastic nonlinear systems," *IEEE Transactions on Systems, Man, and Cybernetics B*, vol. 42, no. 6, pp. 1608–1619, 2012.
- [33] Y. Li, S. C. Tong, and Y. M. Li, "Observer-based adaptive fuzzy backstepping control for strict-feedback stochastic nonlinear systems with time delays," *International Journal of Innovative Computing, Information and Control*, vol. 8, pp. 8103–8114, 2012.
- [34] S. C. Tong, T. Wang, Y. M. Li, and B. Chen, "A combined backstepping and stochastic small- gain approach to robust adaptive fuzzy output feedback control," *IEEE Transactions on Fuzzy Systems*, vol. 21, no. 2, pp. 314–327, 2013.

- [35] H. Q. Wang, B. Chen, and C. Lin, "Adaptive neural tracking control for a class of stochastic nonlinear systems with unknown dead-zone," *International Journal of Innovative Computing, Information and Control*, vol. 9, no. 8, pp. 3257–3270, 2013.
- [36] A. Ferrara and L. Giacomini, "Control of a class of mechanical systems with uncertainties via a constructive adaptive/second order VSC approach," *Journal of Dynamic Systems, Measurement and Control*, vol. 122, no. 1, pp. 33–39, 2000.
- [37] S. S. Ge and C. Wang, "Adaptive NN control of uncertain nonlinear pure-feedback systems," *Automatica*, vol. 38, no. 4, pp. 671–682, 2002.
- [38] D. Wang and J. Huang, "Adaptive neural network control for a class of uncertain nonlinear systems in pure-feedback form," *Automatica*, vol. 38, no. 8, pp. 1365–1372, 2002.
- [39] C. Wang, D. J. Hill, S. S. Ge, and G. Chen, "An ISS-modular approach for adaptive neural control of pure-feedback systems," *Automatica*, vol. 42, no. 5, pp. 723–731, 2006.
- [40] T. P. Zhang and S. S. Ge, "Adaptive dynamic surface control of nonlinear systems with unknown dead zone in pure feedback form," *Automatica*, vol. 44, no. 7, pp. 1895–1903, 2008.
- [41] M. Wang, S. S. Ge, and K.-S. Hong, "Approximation-based adaptive tracking control of pure-feedback nonlinear systems with multiple unknown time-varying delays," *IEEE Transactions on Neural Networks*, vol. 21, no. 11, pp. 1804–1816, 2010.
- [42] H. Q. Wang, B. Chen, X. P. Liu, K. F. Liu, and C. Lin, "Robust adaptive fuzzy tracking control for pure-feedback stochastic nonlinear systems with input constraints," *IEEE Transaction on Cybernetics*, vol. 43, no. 6, pp. 2093–2104, 2013.
- [43] J. J. Yu, K. J. Zhang, and S. M. Fei, "Direct fuzzy tracking control of a class of nonaffine stochastic nonlinear systems with unknown dead-zone input," in *Proceedings of the 17th IFAC World Congress*, pp. 12236–12241, International Federation of Automatic Control (IFAC), Seoul, Korea, 2008.
- [44] Z. Yu, Z. Jin, and H. Du, "Adaptive neural control for a class of non-affine stochastic non-linear systems with time-varying delay: a Razumikhin-Nussbaum method," *IET Control Theory & Applications*, vol. 6, no. 1, pp. 14–23, 2012.
- [45] Y. M. Li and S. C. Tong, "Adaptive fuzzy output-feedback control of pure-feedback uncertain nonlinear systems with unknown dead-zone," *IEEE Transactions on Fuzzy Systems*, 2013.
- [46] S. C. Tong, Y. Li, Y. M. Li, and Y. J. Liu, "Observer-based adaptive fuzzy backstepping control for a class of stochastic nonlinear strict-feedback systems," *IEEE Transactions on Systems, Man, and Cybernetics B*, vol. 41, no. 6, pp. 1693–1704, 2011.
- [47] L. X. Wang and J. M. Mendel, "Fuzzy basis functions, universal approximation, and orthogonal least squares learning," *IEEE Transactions on Neural Networks*, vol. 3, no. 5, pp. 807–814, 1992.
- [48] T. M. Apostol, *Mathematical Analysis*, Addison-Wesley, Reading, Mass, USA, 1963.



Hindawi

Submit your manuscripts at
<http://www.hindawi.com>

